

## CLAIMS

1. Device (1) for anchoring on a wall (2) for the  
securement of elements of any type, preferably subject to  
5 tension, such as shrouds, rigging, cable,

characterized in that the device is present in the form  
of two plates (3, 4) secured to each other, one (3) of these  
plates (3, 4), generally adapted to be applied against the  
internal surface of a wall (2), being secured to a socket  
10 (5) adapted to be positioned facing a hole of said wall (2),  
said socket (5) containing a bundle (6) of flexible fibers  
flared at one end to form at least one layer (6A) gripped  
between the two plates (3, 4), the bundle (6) of fibers  
projecting outside the socket (5) to serve as the anchoring  
15 point for an element of any type connected to the bundle  
(6).

2. Anchoring device (1) according to claim 1,  
characterized in that the plates (3, 4) and the layer  
20 (6A) of fibers are secured together by a binder (7) such as  
a polymerizable resin.

3. Anchoring device (1) according to one of claims 1  
and 2,  
25 characterized in that the socket (5) and the plate (3)  
for application against the wall with which the socket (5)  
is connected, are made in a single piece.

4. Anchoring device (1) according to one of claims 1 to  
30 3,  
characterized in that it is provided, between the  
plates (3 and 4), with a supplemental plate (11), the flared  
fibers of the bundle of fibers extending over a surface of

said intermediate plate before being pushed back against the other surface of said plate.

5      4,      5. Anchoring device (1) according to one of claims 1 to

characterized in that the portion of the bundle (6) passing through the socket (5) is held within a sleeve (8), preferably thermo-shrinkable.

10      5,      6. Anchoring device (1) according to one of claims 1 to

characterized in that the projecting portion (6B) of the bundle (6) of fibers outside the socket (5) has the shape of a loop.

15

6,      7. Anchoring device (1) according to one of claims 1 to

20      characterized in that the socket (5) is threaded within a hole in said wall (2) provided with a female socket (10) to render the device easily movable.

25      8. Anchoring device (1) according to claim 7, characterized in that the socket (5) is screw-threaded so as to coact with the screw-threaded female socket (10) disposed within a hole in the wall (2).

8,      9. Anchoring device (1) according to one of claims 1 to

30      characterized in that the socket (5) is threaded within a hole in the wall (2) whose outlet, on the internal surface side of the wall, is delimited by an annular plate (12) forming the internal surface of the wall against which one of the plates (3) of the device bears.

10. Anchoring device (1) according to claim 9,  
characterized in that the annular plate (12) is  
provided with a throat and/or an annular shoulder serving  
5 for the reception of a toric joint (13) positioned about the  
socket (5) so as to obtain a device connected water-tightly  
to the wall (2).